

Zebra[®] ZXP Series 3[™] Card Printer



SEE MORE. DO MORE.



Zebra's ZXP Series 3 direct-tocard printer provides an array of features, outstanding print quality, and a low cost of ownership. The ZXP Series 3 offers a wide range of high capacity ribbon options, along with the capability to select the card thickness that is right for the application. These features, with the ENERGY STAR® rating, make the ZXP Series 3 the most cost effective card printing solution in its class.

The ZXP Series 3 offers vivid, highquality full color and monochrome printing on single- or dual-sided cards. Operating the ZXP Series 3 is simplified with an intuitive design, color touch points, and quick-replace higher capacity Load-N-Go[™] smart ribbons, which are now eco-friendly using less plastic and more biodegradable material. Zebra's ZRaster[™] host-based image processing technology enables high speed printing without sacrificing image quality.

The printer's compact design makes it the right choice for tight work spaces. Smart card and magnetic stripe encoding options allow the ZXP Series 3 to meet the needs of a variety of markets and applications, including ID and access control cards as well as personalized gift, membership and loyalty cards. Standard Kensington[™] lock feature and optional enclosure lock make the ZXP Series 3 ideal for secure card printing solutions.

Print Touch

The ZXP Series 3 includes Zebra Print Touch™, an embedded Near Field Communication (NFC) chip

and software. Just hold your NFC enabled smartphone up to the Zebra Print Touch logo



on the printer to read key printer information and launch web-based help pages.

Ideal for These Applications

Security / employee ID cards, student ID cards, access control cards

Retail/Hospitality / loyalty cards, gift cards, membership cards

Financial Services / instant issuance financial cards

SPECIFICATIONS AT A GLANCE*

Printer Name

Zebra^{*} ZXP Series 3[™] Card Printer

Printing Specifications

- Dye-sublimation thermal transfer direct to card
- Full color or monochrome printing
- Single- or dual-sided printing
- 700 cph monochrome single-sided
- 180 cph single-sided YMCKO
- 140 cph dual-sided YMCKOK
- Edge-to-edge printing on standard CR-80 media

Standard Features

- True Colours ^{*} ix Series[™] ZXP 3 high-performance ribbons with intelligent media technology
- High capacity, eco-friendly Load-N-Go[™] drop-in
- ribbon cartridges • ZRaster[™] host-based image processing
- Auto calibration of ribbon
- USB connectivity
- OSB connectivity
- Microsoft * Certified Windows * drivers
- ENERGY S TAR CertifiedPrint Touch NFc tag for online printer
- documentation and tools
- 100 card covered feeder (30 mil)
- 45 card capacity output hopper (30 mil)
- 16-character LCD operator control display
- 300 dpi (11.8 dots/mm) print resolution
- Two-year warranty on printer
- Two-year (unlimited passes) original printhead
- One-year hot swap (U.S. only)
- Kensington * secure lock slot

Optional Features

- Built-in 10/100 Ethernet connectivity**
- CardSense[™] single-card feed mode^{**}
- ZebraCare[™] extended product warranty programs
- Lockable enclosure with obscured output bin**

Encoding Options and Specifications

- Magnetic stripe encoder
 - ISO 7811 new and re-encoded, tracks 1,2 and 3, high and low coercivity, stripe down, 30 mil card only
- Smart card contact station
- ISO 7816

ZEBRA

- Combined contact and contactless
- MIFARE ^{*} ISO 14443 (13.56 MHz)**
- ISO 7816 PC/SC compliant**
- EMV level 1 certified**
- 50 card capacity [30 mil] external output hopper**
- Capable of encoding over USB and Ethernet**

Corporate Headquarters

+1 800 423 0442

*Specifications subject to change without notice.

inquirv4@zebra.com

Other Locations / USA:

**Field upgradeable options

Drivers Supported

- Microsoft Windows Certified Printer Drivers: Windows XP, Windows Vista *, Windows Server 2003, Windows Server 2008, Windows 7***, Windows 8***
- ***32 bit and 64 bit compatible

Please see www.zebra.com for up to-date listing of supported systems.

Media Specifications

NOTE : The ZXP Series 3 printer is designed to work only with Zebra True Colours ix Series ZXP 3 high-performance ribbons.

- Zebra ix Series intelligent technology automatically detects and authenticates ribbon.
- Integrated cleaning roller included on each ribbon.
- Media Starter Kit (single-sided) 1 YMCKO
- ribbon, 200 30-mil PVC cards • Optional Cleaning Kit: 4 print engine cleaning
- cards and 4 feeder cleaning cards, 1000 images/card

True Colours ix Series ZXP 3 Ribbon

- YMCKO: 280 images/roll
- 1/2 YMCKO: 400 images/roll
- YMCKOK: 230 images/roll
- KdO: 700 images/roll
- KrO: 700 images/roll
- Black Monochrome: 2000 images/roll
- Red Monochrome: 1700 images/roll
- Blue Monochrome: 1700 images/roll
- Gold Monochrome: 1600 images/roll
- Silver Monochrome: 1600 images/roll
- White Monochrome: 1400 images/roll

Card Compatibility

NOTE: For optimum print quality and printer performance, use of Zebra genuine supplies is recommended.

- Card Thickness: 10-40 mil
- Card Size: CR-80, ISO 7810 format, Type ID-1, 2.12" (54 mm) x 3.38" (86 mm)
- Card Material: PVC and PVC composite
- Smart Card Contact ISO 7816-1,2,3,4
- Smart Card Contactless MIFARE
 Smart Card Contactless MIFARE
- Spot Color or monochrome print only on < 20 mil card thickness

Communications Interfaces

- USB V2.0 (cable included) standard
- Built-in 10/100 Ethernet optional**

Electrical Specifications

- Auto-switching single-phase AC power
- Operating range: 90-132VAC and 190-264VAC RMS
- Frequency range: 47-63 Hz
- Power requirement is 100W maximum continuous
- and 607W peak (for 450 microsec) output power

United Kingdom Asia Pacific: Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, Philippines, Singapore, South Korea, Taiwan, Thailand, Vietnam

EMEA Headquarters

+44 (0)1628 556000

Africa/Middle East:

mseurope@zebra.com

FCC Class A

Asia-Pacific Headquarters

apacchannelmarketing@zebra.com

©2013 ZIH Corp. All product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic and True Colours are registered trademarks of ZIH Corp. All rights reserved. Microsoft, Windows, Windows Vista and Windows Server are either registered trademarks or Microsoft Corporation in the United States and/or other countries. MIFARE is a registered trademark of Philips Semiconductors Gratkom GMBH Luk. Aresington is a registered trademark of Micro ZOB trademarks are demarkation. All other trademarks of the property of their respective owners.

+65 6858 0722

California, Georgia, Illinois, Rhode Island, Texas, Wisconsin

Latin America: Argentina, Brazil, Columbia, Florida (LA Headquarters in USA), Mexico

- Physical Specifications (standard model)
- Height: 9.3" (236 mm)
- Width: 7.9" (200 mm)
- Depth: 14.5" (368 mm)
- Weight: 11.6 lbs (5.3 kg)

Genuine Zebra™ Supplies

Genuine Zebra supplies meet stringent quality standards and are recommended for optimal printing quality and proper printer performance. The ZXP Series 3 card printer is designed to work only with Zebra True Colours™ ix Series ZXP Series 3 highperformance, high capacity ribbons.

CardStudio[™] Software

Zebra's CardStudio[™] is an easy-tolearn, easy-to-operate complete card design and card issuance software suite. It makes designing and printing high quality photo ID cards and other cards easy, with basic to advanced features, and support for all Zebra card printers. For more information, visit www.zebra.com/cardstudio.





www.alphacard.com

(800) 717-8080

Latin America Headquarters

P1032915 (04/13)

+1 847 955 2283

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey,

Dubai, South Africa

inquirv4@zebra.com