



THE PROXCARD PLUS® COMBINATION CARD OFFERS PROXIMITY AND WIEGAND TECHNOLOGIES WITH OPTIONAL PHOTO ID CAPABILITY ON A SINGLE ACCESS

- **Easily Administered** – A cross-reference list correlating the external card number and the programmed ID number provides easy system administration.
- **Security** – Offers over 137 billion unique codes.
- **Long Life** – Dual battery design and low current draw allows two to five years with typical usage.
- **Durability** – Rugged, UV-resistant, sonic-welded polycarbonate case is also weather resistant.

Features:

- Provides a four to eight foot read range.
- Velcro backing attaches easily to interior of vehicle windshield.
- Attractive, durable sealed case.
- Compatible with MaxiProx® reader and all HID card formats.
- Two to five year battery life, depending on usage.
- Competitively priced as compared to VHF vehicle tags.

The ProxPass® is an active tag specifically designed for vehicle access control. Providing convenient access control for parking and fleet management applications, ProxPass is an ideal augmentation to an existing or new HID proximity installation. It can be encoded with any HID format and numbering system used by HID proximity cards, including the Corporate 1000 format.

SPECIFICATIONS

ProxPass® Active Tag

Typical Maximum* Read Range	Up to 6' (2 m)
Dimensions	3.625" x 2.65" x 0.30" (9.25cm x 6.75cm x .76cm)
Mounting Location	Interior windshield, driver's side, upper or lower corner Note: Ideal mounting location is on interior windshield glass. Mounting on metal will degrade performance.
Operating Temperature	-22° to 185° F (-30° to +85° C)
Options	External card numbering
Environmental	5 - 95% RH, non-condensing (Not for marine usage)
Warranty	Lifetime

NOTES:

*Dependent on local installation conditions.

